

LL500

Applications

- Checking and adjusting elevations
- Taking grade shots
- Excavating cutting depth
- Basement excavation
- Digging septic tanks
- Checking foundations
- Digging footings
- Setting forms
- Checking sub-base materials
- Screeding concrete
- Slope on grade



Rugged, Reliable Laser Leveling Systems



Setting the Industry Standard

Accurate, stable and very reliable, the Spectra Precision® Laser LL500 is the ideal one-person leveling system for a range of everyday elevation measurements on the construction site.

Designed for use on the jobsite, and reliable even in the harshest of conditions, today more contractors around the world use Spectra Precision Lasers to increase productivity and profitability.

One Laser Levels Your Entire Work Area

The LL500 transmitter sends a continuous, self-leveled 360-degree laser reference over a work area, up to a 500-meter (1,600-foot) diameter. With the LL500, you can perform any two-person leveling task with just one person. Simply set up the laser transmitter anywhere on your job site; it transmits a laser beam to provide an elevation reference that can be picked up by one or more laser receivers, including our innovative HL700 or CR700, whether they are handheld, attached to a grade rod or mounted on a machine.

Key Features

- 1,650 ft (500 m) working diameter which increases productivity by reducing need for multiple set-ups on a large job site
- Self-leveling with built-in 'out-of-level' shut off that maintains accuracy over the entire work area, and minimizes errors
- High accuracy laser, 1/16 in per 100 ft (1.5 mm per 30 m) with temperature compensation provides highly stable, repeatable accuracy even under large temperature changes
- Uses alkaline or rechargeable batteries—so you are less likely to run out of power and the unit keeps working with no downtime due to power loss
- Visible 'spotting' beam for determining receiver mounting placement making it faster to find the on-grade position
- Comes with a choice of HL700 or CR700 receivers allowing you to choose the best option to suit your application
- 5 Year warranty

User Benefits

- Temperature compensation allows you to meet your toughest accuracy requirements in any type of variable environmental conditions
- Reduces the amount of time required for each grade shot, so more grade shots are taken for increased accuracy
- Eliminates rework caused by miscommunication or out-of-level instruments with built-in out-of-level warning and shut-off
- Immediately locates the laser plane with the visible spotting beam



Rugged, Reliable Laser Leveling Systems

LL500 Specifications

- Leveling accuracy^{1,3}: ± 1.5 mm/30 m, 1/16" @ 100 ft, 10 arc seconds
- Operating diameter^{1,2}: appr. 500 m (1600 feet)
- Self-leveling range: ± 11 arc minutes
- Temperature Compensation: Yes
- Laser type: 670 nm
- Laser class : Class 2
- Compensation Type: Wire Hung, Air Damped
- Power source: 4x D-Cell Alkaline or NiMH batteries
- Battery life¹: 100 hours NiMH
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Storage temp.: -20°C to 70°C (-4°F to 158°F)
- Tripod attachments: 5/8 x 11 horizontally
- Dust and waterproof: Yes - IP54
- Weight: 3.6 kg (8 lbs)
- Warranty: 5 Years

HL700 Digital Readout Receiver

- Digital readout of elevation shows how far from on grade without moving the rod clamp
- Large 127 mm (5 inch) reception height acquires the beam quickly and keeps you in the laser beam
- CAPTURE function remotely acquires and retains a measurement when the display is difficult to see
- Extremely tough - can withstand a drop of 3 m (10 ft) onto concrete and has a 3 year warranty to back it up
- Key Features:
 - Digital readout of elevation
 - Exact distance from grade displayed
 - Anti-strobe sensor to prevent false reading from jobsite strobe lights
 - Large reception height to ease beam reception
 - Withstands a drop of up to 3 m (10 ft)
- User Benefits:
 - No need to go "on-grade" to measure;
 - Saves considerable time
 - Reduces rework by allowing remote monitoring
 - Increases reliability, accuracy and durability

CR700 Receiver

- Simultaneous green and red LED display ensures that information can be read even in poor light, over long distances, and at an angle
- Magnetic mount is included for fast machine mounting and holds the receiver firmly in place
- The CR700 wraparound receiver cells offer continuous pickup through an operating range of 200° for reduced setups and improved productivity, especially in machine applications

CR700 Receiver Specifications

- On-grade sensitivities:
 - Super Fine 0.5 mm (~1/32 in)
 - Fine 1 mm (~1/16 in)
 - Medium 2 mm (~1/8 in)
 - Coarse 5 mm (~1/4 in)
 - Machine Fine 10 mm (~1/2 in)
 - Machine Coarse 25 mm (~1 in)
- Reception height: 127 mm (5 inches)
- Operating temp.: -20°C to 60°C (-4°F to 140°F)
- Battery life¹ (3 x AA): 60+ hours at normal operation
- Auto shut-off: 30 minutes
- Reception Angle: 200 degrees
- Dust and waterproof: Yes
- Weight: 0.5 kg (1.1 lbs)
- Warranty: 3 Years

HL700 Digital Readout Receiver Specifications

- Digital readout units: mm, cm, ft, in, frac. in
- Reception height: 127 mm (5 inches)
- Six On-grade sensitivities:
 - Ultra Fine 0.5 mm (~1/32 in)
 - Super Fine 1 mm (~1/16 in)
 - Fine 2 mm (~1/8 in)
 - Medium 5 mm (~1/4 in)
 - Coarse 10 mm (~1/2 in)
 - Calibration Mode 0.1 mm (~1/64 in)
- Battery life¹ (2 x AA): 60+ hours continuous operation
- Auto shut-off: 30 minutes/24 hours
- Operating temp.: -20°C to 50°C (-4°F to 122°F)
- Dust and waterproof: Yes - IP67
- Weight: 0.37 kg (13.1 oz)
- Warranty: 3 Years

⁽¹⁾ at 21° Celsius (70° F)
⁽²⁾ under optimal atmospheric circumstances
⁽³⁾ along the axis



LL500 - Setting the Industry Standard



CR700 Combination Receiver can be machine or rod mounted for increased productivity applications



HL700 Digital Readout Radio Receiver to measure and display beam location

Contact Information:

AUSTRALIA
Vantage Australia
33 Allison Street, Bowen Hills Q 4006
Phone: 1800 482 682
Vantage-au.com/Spectra Precision

To locate your nearest distributor, please visit the Dealer Locator section at vantage-au.com/spectraprecision
Specifications and descriptions are subject to change without notice.

© 2025, Spectra Precision (USA) LLC. All rights reserved. Spectra Precision is a trademark Spectra Precision (USA) LLC, registered in the United States Patent and Trademark office and in other countries. All other trademarks are the property of their respective owners.

PN 022507-632 Rev A (01/25)

